

## Tablet Specifications

Item	Description
<b>Tablet Operating System</b>	Android™ 4.4.2, KitKat
<b>Tablet Processor</b>	Samsung Exynos Six-core Processor (1.3GHz Quad-core ARM Cortex-A7 + 1.7GHz Dual-core ARM Cortex-A15)
<b>Tablet Memory</b>	2GB RAM & 64GB On-board Memory
<b>Tablet Display</b>	9.7-inch LED capacitive touch screen with 1024x768 resolution
<b>Tablet Connectivity</b>	Wi-Fi (802.11 a/b/g/n/ac) USB: 2.0 BT v.2.1 + EDR SD Card (Support up to 32GB) HDMI
<b>Tablet Camera (rear)</b>	8.0 Megapixel, AF with Flashlight
<b>Tablet Sensors</b>	Gravity Accelerometer, Ambient Light Sensor (ALS)
<b>Tablet Audio</b>	Microphone
<b>Input/output</b>	Dual Speakers 3-Band 3.5 mm stereo/standard headset jack
<b>Tablet Power and Battery</b>	11000 mAh 3.7 V lithium-polymer battery Charging via 12 V AC/DC power supply with the temperature between 0°C and 45°C
<b>Tablet Input Voltage</b>	12 V (9-24 V)
<b>Tablet Power Consumption</b>	6.5 W
<b>Tablet Operating Temp.</b>	0 to 50°C (32 to 122°F)
<b>Tablet Storage Temp.</b>	-20 to 60°C (-4 to 140°F)
<b>Tablet Dimensions (WxHxD)</b>	300 mm (11.81") x 220 mm (8.66") x 50 mm (1.97")
<b>Tablet Weight</b>	NW: 1.42 kg (3.13 lb.) GW: 8.655 kg (19.08 lb.)
<b>Tablet Protocols</b>	ISO 9142-2, ISO 14230-2, ISO 15765-4, K/L-Line, Flashing Code, SAE-J1850 VPW, SAE-J1850 PWM, CAN ISO 11898, Highspeed, Middlespeed, Lowspeed and Singlewire CAN, GM UART, UART Echo Byte Protocol, Honda Diag-H Protocol, TP 2.0, TP 1.6, SAE J1939, SAE J1708, Fault-Tolerant CAN

## Calibration Frame & Pattern Board Specifications

<b>Item</b>	<b>Description</b>
<b>Calibration Frame Dimensions (WxDxH)</b>	2510mm (98.82") x 714mm (28.11") x 1480-2105 mm (58.27-82.87")
<b>Calibration Frame Weight</b>	NW: 74.5 kg (164.24 lb.) GW: 152kg (335.1 lb.)
<b>Pattern Board Size (LxW)</b>	1360mm (53.54") x 960mm (37.80")
<b>Crossbar Length</b>	2510mm (98.82")
<b>Measurement Range of Crossbar's Height</b>	Height min=350mm (13.78") Height max=950mm (37.40")
<b>Measurement Range of Pattern Board 's Height</b>	Height min=1000mm (39.37") Height max=1600mm (62.99")
<b>Rated Power</b>	24 V, 3A
<b>Laser Rated Power</b>	3V, 25mA
<b>Laser Battery Type</b>	AA 2x1.5V
<b>Calibration Frame Working Temp.</b>	0°C to 50°C
<b>Calibration Frame Storage Temp.</b>	-20°C to 60°C
<b>Laser Class</b>	Class 2
<b>Certification</b>	CE, FCC, RoHS